



www.sherwin-williams.com

108.08

PREPRITE™ HIGH BUILD

INTERIOR LATEX PRIMER/SURFACER

B28W601

CHARACTERISTICS

- Fills and surfaces rough and uneven new **drywall** construction
- Uniforms various porosities between **dry-wall paper** and **joints**
- Ensures the finish coat will be a smooth and uniform sheen
- Minimizes minor surface imperfections: paper fuzz, minor sanding grooves, nicks, pinholes.

Use on interior:

- Drywall
- Cured Plaster
- Under Decorative Texture Finishes

Color: White

Coverage:

can be applied from:

400 sq ft/gal @ 4 mils wet; 0.8 mils dry to:

80 sq ft/gal @ 20 mils wet; 4.4 mils dry

Drying Time, @ 77°F, 50% RH:

temperature and humidity dependent

Touch: 1 hour

Recoat: 4 hours

Flash Point: N/A

Finish: 0-10 units @ 85°

Solvent/Reducer: Water

Vehicle Type: Vinyl Acrylic

B28W601

VOC: 71 g/L; 0.60 lb/gal

Volume Solids: 23 ± 2%

Weight Solids: 40 ± 2%

Weight per Gallon: 10.6 lb

Tinting - For better hiding of deeper colors, use up to 2 oz per gallon of Blend-A-Color Toner to approximate the topcoat color. Check color before use. Six minutes minimum mixing on a mechanical shaker is required for complete mixing of color. Check color before use.

APPLICATION

Apply at temperatures above 50°F.

No reduction necessary.

Brush - Use a nylon/polyester brush.

Roller - Use a 3/8" - 3/4" nap synthetic roller cover.

Spray—Airless

Pressure 2000 psi

Tip017" - .021"

Use a coarse filter, 30-40 mesh

Other Uses

To produce a smooth, economical latex wall primer, up to 1 gallon of water can be added to 5 gallons of Primer/Surfacer.

Box thoroughly to a uniform consistency.

To make a thicker surfacer, High Build can be mixed with drywall compounds. The types of compound that can be mixed with High Build are pre-mixed, all purpose and topping compounds. **DO NOT USE QUICK SET COMPOUNDS, THEY WILL CAUSE THE FILM TO CRACK AND PEEL!** Box thoroughly to a uniform consistency.

The following mixes will increase surface build and improve holdout when texturing walls and ceilings:

Spray applied skim coat:
2 parts compound, 1 part High Build

Hopper sprayed spatter texture:
3 or 4 parts compound, 1 part High Build

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Use on new, bare drywall construction

Joint compound must be thoroughly dry and sanded smooth. Repair any significant surface damage, cracks, holes, etc. Remove all sanding dust and construction dust by sweeping or vacuuming. Seal stains from water, ink, pencil, grease, etc. with PrepRite ProBlock Primer Sealer.

Caulking

Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with Pro Select™ Premium Sili-conized Acrylic Latex Caulk 1100A after priming the surface.

Special Recommendations

When topcoating with enamels, 2 top-coats are required for full sheen development, reducing the potential for areas of uneven sheen when touching up.

108.08



PREPRITE™ HIGH BUILD

INTERIOR LATEX PRIMER/SURFACER

B28W601

CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

For interior use only.
Protect from freezing.

LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, Call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. LCE 10/19/01 B28W601 03 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.